



Marineco Ltd
Gilston Road, Saltash Industrial Estate
Saltash PL12 6LF

TECHNICAL DATA SHEET: LUBRICANTS

TOPLUBE SUPER 15W40

DESCRIPTION

Toplube Super 15W40 is an SHPD (Super High Performance Diesel) engine oil manufactured to an approved formulation to give exceptional performance even at extended drain intervals.

Toplube Super 15W40 is a tried and tested product that has given many years of trouble free service within the marine, agricultural, road haulage and plant hire industries.

APPLICATIONS

In today's high-speed, increased horsepower, severe-duty diesel engines, motor oils are stressed as never before and must serve many functions simultaneously. In addition to its primary function of lubricating moving parts to minimize friction and wear, the oil must keep the engine clean and free of rust, prevent corrosion of bearings, act as a coolant and trap contaminants to be carried in suspension until the oil is drained.

Toplube Super 15W40 has been specifically formulated to meet these challenges.

BENEFITS

Toplube Super 15W40 meets a wide range of OEM and industry specifications allowing it to be used across mixed fleets.

SPECIFICATIONS

ACEA E7	API CH-4/CF	API SJ
MTU Type 2	Cummins CES 20076/77	Volvo VDS-3
Caterpillar ECF-1a	Mack EO-N & EO-M Plus	MB 228.3
MAN 3275	Renault RLD/RLD-2	Detroit Diesel 93K215